
Subject: Re: propulsion

Posted by [Joerg von Lingen](#) on Tue, 12 Jul 2005 12:52:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

Martin,

I have notified this drawback. Subsequently I have changed the occurrence of <propulsion> element to unbounded, thus one <propulsion> element can be used for each power supply system.

```
<xsd:element ref="propulsion" minOccurs="0" maxOccurs="unbounded">
  <xsd:annotation>
    <xsd:documentation>technical data about the propulsion system of a
vehicle</xsd:documentation>
    <xsd:documentation>History: V0.91 First release
V0.92 extensive revision, adding all subsystems of propulsion
V0.93 change to user defined type
V1.01 changed to refer to the global element and can occur "unbounded" each for one power
supply system</xsd:documentation>
  </xsd:annotation>
</xsd:element>
```

The new schema version will be published in due course.

Regards,

Jörg von Lingen

Martin Jacob wrote the following on 22.06.2005 11:05:

```
> Hello,
>
> at the moment it is possible to add only one propultion to a engine. I will suggest to use the
element propultion as
> much as necessry for a engine. It will be usefull for engines which can operate in multiple
power supply systems, e.g.
> 16,7Hz/15kV and 50Hz/25kV.
>
> Martin
```