
Subject: loading gauge

Posted by [Torben Brand](#) on Wed, 29 Nov 2017 09:52:53 GMT

[View Forum Message](#) <> [Reply to Message](#)

I have been asked by Christian Rahmig to produce the enumeration list for the Norwegian loading gauge for railML3. We have three value list. One international based on a UIC standard. One national based on CEN standard 15273 (with only one value) and one national loading gauge value (with also only one value). Thus we should be able to define one or more defined enumeration list (international/national). The values are defined on a line section level.

Our Norwegian values are:

Name of Norwegian list: "Internasjonal profil"

Suggestion for univocal enumeration UUID: "UIC-596-5"

List values (as used/listed in Norway [http://orv.jbv.no/ns/doku.php?id=vedlegg:internasjonal_profi](http://orv.jbv.no/ns/doku.php?id=vedlegg:internasjonal_profil)l):

P80

P77

P73

P70

P60

C80

C77

C73

C70

C60

P410

P407

P403

P400

P390

C410

C407

C403

C400

C390

Not verified

Name of Norwegian list: "JBV NO1 - prEN 15273 Dynamisk profil"

Suggestion for univocal enumeration UUID: "EN-15273"

List values (as used/listed in Norway

http://orv.jbv.no/ns/doku.php?id=vedlegg:jbv_no1_-_pren_15273_dynamisk_profil):

NO1

Name of Norwegian list: "Multipurpose profil"

Suggestion for univocal enumeration UUID: "NO:TRV-520-5-5a"

[https://trv.jbv.no/wiki/Underbygning/Prosjektering_og_byggin](https://trv.jbv.no/wiki/Underbygning/Prosjektering_og_byggin_g/Profiler_og_minste_tverrsnitt/Vedlegg/Profiler)
[g/Profiler_og_minste_tverrsnitt/Vedlegg/Profiler](https://trv.jbv.no/wiki/Underbygning/Prosjektering_og_byggin_g/Profiler_og_minste_tverrsnitt/Vedlegg/Profiler)

List values (as used/listed in Norway

http://orv.jbv.no/ns/doku.php?id=vedlegg:multipurpose_profil):

Multipurpose

JBV-L
